



Article : 900025

Product : Total power grease

Description

PRO-Tech Total Power Grease is a high quality grease that is ideal as a universal lubricant due to its excellent pressure and temperature resistance. Initially it is a liquid when applied so it can penetrate deeply between the parts. Once the solvent has evaporated, solid and pressure-resistant grease remains. Due to these characteristics PRO-Tech Total Power Grease is ideally suited for lubricating components where metal rubs against metal.

Specifications

- ❖ Contents: 500 ML NET
- ❖ Base: Mineral oil, lithium soap and EP additives
- ❖ Appearance: Light brown grease
- ❖ Propellant: Propane-Butane
- ❖ VOC-CH %:82%
- ❖ VOC-EU g/l:539 g/l
- ❖ Specific gravity (g/ml 20°C):0.658
- ❖ Vapour pressure at 20°C:2.5-3.1 bar
- ❖ Spraying flow rate:1.8 g/sec
- ❖ Temperature resistant: -40°C to +170°C
- ❖ Distribution:1 box of 12 products
- ❖ Multidirectional

General condition

For optimal performance, it should be applied to a clean dry surface at a temperature between 5°C and 30°C.

Must be kept in a frost-free place.

Stored as given above, the average storage period is approximately one year.

Avoid exposure to temperatures above 50°C and keep away from sources of ignition, heat and sunlight.

As with all handling and storage operations, NO SMOKING is very strongly recommended.



Instructions for use

Ideally clean the surface with PRO-Tech Power cleaner before proceeding. The aerosol can should be at room temperature. The ideal processing temperature is from 5 to 30°C. Shake the aerosol can before use. Apply PRO-Tech Total Power Grease to the desired surface. The specific lubricating property is achieved after evaporation of the solvent (approximately one minute).

Application

- ❖ Metal on metal
- ❖ Hinges
- ❖ Door catchers
- ❖ Sprockets
- ❖ Window mechanisms
- ❖ Pedals
- ❖ Hinges
- ❖ Brake parts
- ❖ Bearings

The SOPPEC PRO TECH ranges offer a wide choice of products in aerosol format, grouped according to function: PROTECTION, CLEANING, LUBRICATION !

SOPPEC ZI NERSAC
16440 NERSAC
FRANCE
Tel : +33(0)5 90 93

Distribué par :
Distributed by :

TECHNIMA CENTRAL GmbH
KREUZERWEG 13
77955 ETTENHEIM
ALLEMAGNE
Tel : + 49-(0) -7822-789 00 11

CIA TECHNIMA SUD EUROPA SRL
VIA S. BRIGIDA N.43
10060 ROLETTA (TO)
ITALIE
Tel : +39 0121 542 542

TECHNIMA NORDIC AB
KROKSLÄTTTS TORG 5
431 37 MÖLNDAL,
SUEDE
Tel : +46 (0)31 10 21 90