

LUMBERJACK III NEO

Forest safety boots in natural rubber with chainsaw cut protection LEVEL 3
4mm neoprene lining, steel toe cap

This PPE has been subjected to an EU-type examination in accordance with PPE new regulation 2016/425. Tested and certified by CTC, Lyon/France - NB 0075. It satisfies essential health and safety requirements,

standards EN ISO 20345:2011 / EN ISO 17249:2013 / SB E CI SRA

Technical data

LUMBERJACK III NEO



Outsole FOREST:

in nitrile rubber, with robust tread

SRA slip resistance on tiling floor

Size range: 37 to 48

Origin EU

Characteristic PPE LEVEL 3 chainsaw protective material resistant up to 28m/s

Protection fabric Material: 55 % polyester 45 % polyamide
Knitting: Circular knit
Weight: 370 g/m²

KWF Test "PROFI"

Classification II : by the material / Natural rubber
Design D : knee height boot

Manufacturing process Vulcanized / Hand made

Basic requirements SB

Toe-cap steel, impact resistance 200 joules
compression resistance 15 kN

Additional requirement Energy absorption of heel area (E)
Cold resistance (CI)

Lining 4mm high quality green neoprene lining

Colour Orange / Green



LUMBERJACK III NEO
by EPM
CE 0075
EN ISO 20345 : 2011
EN ISO 17249 : 2013
SB E CI SRA
Level 3
KWF

