

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2019/06/24

n. 644192601/OE

Validity: 2024/06/23

This Certificate cancels & replaces the previous one nº 644151302/OE dated 2015/03/23

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Test report:	RCT n°3832106.01/E
Technical File:	DC-10470/E
Size range:	from 38 to 48
Intended use:	woodcutters, forest rangers, farmers and alike (foot protection for works implying the u of a chainsaw)
	EN ISO 17249:2013 (UNI EN ISO 17249:2014) Safety footwear with resistance to chain saw cutting
	(UNI EN ISO 20345:2012) EN ISO 20344:2011 Personal protective equipment – Test methods for footwe (UNI EN ISO 20344:2012)
Technical Standard:	and 48. EN ISO 20345:2011 Personal protective equipment – Safety footwear
	serves as penetration resistant insert; removable insock: grey perforated foam material coupled with non-woven material contact with the foot (code R29); toecap: steel, art. 2443 SMAL for the sizes from 38 to 46, art. 1604 SMAL for the sizes
	Tepor Pidigi), that covers also the insole; <u>collar lining</u> : black mesh fabric (code Solar Pidigi); <u>insole</u> : multilayered fabric TEXON ENIGMA ZERO HT2 with a black printing, <u>which a</u>
	reinforced with upper's leather; <u>vamp and quarter lining</u> : grey herringbone fabric coupled with a membrane (co
	rear collar: black fabric "Lycra" coupled with foam material, total thickness 3,5 m (code LVG) folded in on itself; tongue/bellows: "Cordura" black fabric (code FCDP), lined and centrally padde
	<u>collar</u> : two different pieces of synthetic coated material (one black colour and one recolour), perforated (code SCG874);
	TNGDB/TNNDB), black coated leather (code MLCA) with cutting-resistant insert, wh high-strength fabric art. AT8 ENGTEX (8 layers);
	sole: black nitril rubber with a red oval mark in the plantar arch, marked "ANTISTAT NITRIL SOLE OIL & PETROL RESISTANT" (code OREGON); upper: grey and black fabric "Nubuk", declared thickness 2,0/2,2 mm (cod
Description:	design: C (half-knee boot); fastening system: by means of laces; processing: AGO;
Model	" 295469" FIORDLAND
Category of PPE:	III : "severe" risks. The validity of the present certificate is to be reconfirmed with the annual production surveillance report issued by the authorized Notified Body, as per annex VII of the Regulation (module C2).
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I + EN ISO 17249:2013 again mechanical chainsaw cutting (= footwear in leather and other materials
(Responsible of the PPE)	5 Rue Emile Francqui 1435 Mont Saint Guibert – Belgium
Manufacturer:	BL <mark>O</mark> UNT EUROPE SA



Certificato ue E rev04 - 19/04/18



PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2019/06/24

n. 644192601/OE

Validity: 2024/06/23

	202 17 007 20
Functions and performance levels:	basic requirements for safety footwear (see Table 2 and 3 of EN ISO 20345:2011): al mandatory ones, among which:
	SRC = Slip resistance – meets the following requirements:
	- <u>surface</u> : ceramic / <u>lubricant</u> : detergent solution;
	- <u>surface</u> : smooth steel / <u>lubricant</u> : glycerine.
	Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011): S3 = closed seat region, antistatic properties, energy absorption of seat region,
	resistance to fuel oil of the outsole, water penetration resistance and absorption (water-
	repellent upper), penetration resistance, cleated outsole; WR = water resistant of the
	whole footwear; HRO = resistance to hot contact of the outsole; HI = heat insulation of the outsole; CI = cold insulation of the outsole.
	Furthermore the footwear meets the requirements for footwear with resistance to chain
	saw cutting (see EN ISO 17249:2013) – LEVEL: 2 (chain speed: 24 m/s).
	Note: the penetration resistance of the synthetic stitch proof insole tends to decrea <mark>se with the</mark> diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).
Marking:	 On a label stitched onto the tongue and including the following information: CE Marking + number of the Notified Body in charge of the annual control of the PPE; registered Trademark (OREGON) + complete address of the Manufacturer; identification of the product (= art. code nr.) + country code (B); size of the footwear; month and year of production; nr./year of the two Technical Standards of reference + safety symbols; pictogram referred to the EN ISO 17249 with indication of the LEV. reached (on the external side of the footwear; additional info: batch number, "made in".
OREG	
L	.ot.MT81
29546	9 06/19
B((E 0498
EN ISO 20	345:2011
EN ISO 17	
	HRO-HI-SRC
Made in R	
	Europe S.A.
	Francqui,5
B 1435 Mo	ont Saint Guibert

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).



Certificato ue E rev04 - 19/04/18

Belgium