


TUBOGPRO2C

HOSE PRO SERIES - 2 WIRE BRAIDS 2SC

TUBO SERIE PRO - 2 TRECCE 2SC



Norm - Norma: EN 857 2SC

| Code Codice | ø Inside ø Interno | | ø Out ø Est | Work. Press. Press. Eser | | Burst Scoppio | Radius Raggio | Weight Peso |
|----------------|-----------------------|---------|----------------|-----------------------------|------|------------------|------------------|----------------|
| | Inch/Pollici | DN (mm) | mm | bar | psi | bar | mm | kg/mt |
| TUBOG04PRO2C | 1/4 | 6 | 13,4 | 400 | 5800 | 1600 | 75 | 0,28 |
| TUBOG05PRO2C | 5/16 | 8 | 15,2 | 350 | 5000 | 1400 | 85 | 0,34 |
| TUBOG06PRO2C | 3/8 | 10 | 17,4 | 330 | 4800 | 1320 | 90 | 0,41 |
| TUBOG08PRO2C | 1/2 | 12 | 20,7 | 275 | 4000 | 1100 | 130 | 0,56 |
| TUBOG10PRO2C | 5/8 | 16 | 24 | 250 | 3625 | 1000 | 170 | 0,64 |
| TUBOG12PRO2C | 3/4 | 19 | 28 | 215 | 3100 | 860 | 200 | 0,81 |
| TUBOG16PRO2C | 1" | 25 | 35,3 | 165 | 2400 | 660 | 250 | 1,25 |

notes

TUBE:
SYNTHETIC RUBBER, RESISTANT
AGAINST HYDRAULIC FLUIDS
REINFORCEMENT:
TWO BRAIDS OF HIGH TENSILE
STEEL WIRE
COVER:
SMOOTH SYNTHETIC RUBBER, MSHA
APPROVED
TEMPERATURE RANGE (FLUID):
FROM -40°C TO 100°C